

CP6613 - The most robust pneumatic nutrunner in its class with 960 ft.lbs / 1,300 Nm max.



### Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm
- ▶ Lightweight

### Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6613	
Part number	6151800090	
Square drive	3/4"	19 mm
Length	254 mm	10"
Net weight	3.7 kg	8.3 lb
Height	212 mm	8.34"
Width	72 mm	2.83"
Side to center	32 mm	1.26"
Free speed air consumption	23 l/s	48 cfm
Min. hose size	13 mm	1/2"
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s <sup>2</sup>	

<b>Reaction bar</b>	S-type	
<b>Reversible</b>	Reversible	
<b>Torque preset #</b>	Multi	
<b>Square drive</b>	3/4"	19
<b>Handle type</b>	Pistol	
<b>Free speed</b>	20 rpm	
<b>Working Torque Range (fwd)</b>	320 - 1300 Nm	236 - 960
<b>Working Torque Range (reverse)</b>	320 - 1300 Nm	236 - 960
<b>Maximum Torque (fwd)</b>	1300 Nm	960 <i>ft.lbs</i>
<b>Maximum Torque (reverse)</b>	1300 Nm	960 <i>ft.lbs</i>
<b>Socket retainer</b>	Hole	
<b>Square drive</b>	19 mm	3/4"
<b>Bolt size</b>	20-27	3/4 - 1-1/16
<b>European Directives</b>	2006/42/EC (17/05/2006)	
<b>European Standards</b>	EN ISO 11148-6:2013	
<b>Weight Including Reaction Arm</b>	4.4 kg	10.1 <i>lb</i>
<b>Weight w/o Reaction Arm</b>	3.7 kg	8.3 <i>lb</i>

**CP6613 + ATC PACK - The most robust pneumatic nutrunner in its class with 960 ft.lbs / 1,300 Nm max. and our most accurate air supply solution**



### Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm
- ▶ Lightweight

### Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
<b>Model</b>	CP6613 + ATC PACK	
<b>Part number</b>	6151800120	
<b>Square drive</b>	3/4"	19 mm
<b>Length</b>	254 mm	10"
<b>Height</b>	212 mm	8.34"
<b>Width</b>	72 mm	2.83"
<b>Side to center</b>	32 mm	1.26"
<b>Free speed air consumption</b>	23 l/s	48 cfm
<b>Min. hose size</b>	13 mm	1/2"
<b>Sound pressure</b>	90 db(A)	
<b>Sound Power</b>	101 db(A)	
<b>European Sound standard</b>	ISO 15744	
<b>Sound uncertainty</b>	3 db(A)	
<b>Vibration ISO</b>	ISO 28927-2	
<b>Vibration</b>	<2,5 m/s <sup>2</sup>	

<b>European Directives</b>	2006/42/EC (17/05/2006)	
<b>European Standards</b>	EN ISO 11148-6:2012	
<b>Reaction bar</b>	S-type	
<b>Reversible</b>	Reversible	
<b>Torque preset #</b>	Multi	
<b>Square drive</b>	3/4"	19
<b>Handle type</b>	Pistol	
<b>Free speed</b>	20 rpm	
<b>Working Torque Range (fwd)</b>	320 - 1300 Nm	236 - 960
<b>Working Torque Range (reverse)</b>	320 - 1300 Nm	236 - 960
<b>Maximum Torque (fwd)</b>	1300 Nm	960 <i>ft.lbs</i>
<b>Maximum Torque (reverse)</b>	1300 Nm	960 <i>ft.lbs</i>
<b>Socket retainer</b>	Hole	
<b>Square drive</b>	19 mm	3/4"
<b>Bolt size</b>	20-27	3/4 - 1-1/16
<b>European Standards</b>	EN ISO 11148-6:2013	
<b>Weight Including Reaction Arm</b>	4.4 kg	10.1 <i>lb</i>
<b>Weight w/o Reaction Arm</b>	3.7 kg	8.3 <i>lb</i>

**CP6626 + ATC PACK - The most robust pneumatic nutrunner in its class with 1,900 ft.lbs / 2,600 Nm max. and our most accurate air supply solution**



### Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

### Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description	
<b>Model</b>	CP6626 + ATC PACK
<b>Part number</b>	6151800130
<b>Length</b>	300 mm      12"
<b>Height</b>	212 mm      8.34"
<b>Width</b>	72 mm      2.32"
<b>Side to center</b>	34 mm      1.34"
<b>Sound pressure</b>	90 db(A)
<b>Sound Power</b>	101 db(A)
<b>European Sound standard</b>	ISO 15744
<b>Sound uncertainty</b>	3 db(A)
<b>Vibration ISO</b>	ISO 28927-2
<b>Vibration</b>	<2,5 m/s <sup>2</sup>
<b>European Directives</b>	2006/42/EC (17/05/2006)
<b>European Standards</b>	EN ISO 11148-6:2012
<b>Reaction bar</b>	S-type
<b>Reversible</b>	Reversible

<b>Torque preset #</b>	Multi	
<b>Square drive</b>	1"	25 mm
<b>Handle type</b>	Pistol	
<b>Free speed</b>	10 rpm	
<b>Working Torque Range (fwd)</b>	700 - 2600 Nm	520 - 1900
<b>Working Torque Range (reverse)</b>	700 - 2600 Nm	520 - 1900
<b>Maximum Torque (fwd)</b>	2600 Nm	1900 ft.lbs
<b>Maximum Torque (reverse)</b>	2600 Nm	1900 ft.lbs
<b>Socket retainer</b>	Hole	
<b>Square drive</b>	25 mm	1"
<b>Bolt size</b>	20 - 36	3/4 - 1 3/8
<b>European Standards</b>	EN ISO 11148-6:2013	
<b>Weight Including Reaction Arm</b>	6.5 kg	14.3 lb
<b>Weight w/o Reaction Arm</b>	5.1 kg	11.2 lb

**CP6626 - The most robust pneumatic nutrunner in its class with 1,900 ft.lbs / 2,600 Nm max.**



### Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

### Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
<b>Model</b>	CP6626	
<b>Part number</b>	6151800100	
<b>Length</b>	300 mm	12"
<b>Net weight</b>	5.1 kg	11.2 lb
<b>Height</b>	212 mm	8.34"
<b>Width</b>	72 mm	2.83"
<b>Side to center</b>	34 mm	1.34"
<b>Sound pressure</b>	90 db(A)	
<b>Sound Power</b>	101 db(A)	
<b>European Sound standard</b>	ISO 15744	
<b>Sound uncertainty</b>	3 db(A)	
<b>Vibration ISO</b>	ISO 28927-2	
<b>Vibration</b>	<2,5 m/s <sup>2</sup>	
<b>European Directives</b>	2006/42/EC (17/05/2006)	
<b>European Standards</b>	EN ISO 11148-6:2012	
<b>Reaction bar</b>	S-type	

<b>Reversible</b>	Reversible	
<b>Torque preset #</b>	Multi	
<b>Square drive</b>	1"	25 mm
<b>Handle type</b>	Pistol	
<b>Free speed</b>	10 rpm	
<b>Working Torque Range (fwd)</b>	700 - 2600 Nm	520 - 1900
<b>Working Torque Range (reverse)</b>	700 - 2600 Nm	520 - 1900
<b>Maximum Torque (fwd)</b>	2600 Nm	1900 ft.lbs
<b>Maximum Torque (reverse)</b>	2600 Nm	1900 ft.lbs
<b>Socket retainer</b>	Hole	
<b>Square drive</b>	25 mm	1"
<b>Bolt size</b>	20 - 36	3/4 - 1 3/8
<b>European Standards</b>	EN ISO 11148-6:2013	
<b>Weight Including Reaction Arm</b>	6.5 kg	14,3 lb
<b>Weight w/o Reaction Arm</b>	5.1 kg	11.2 lb



**CP6641 + ATC PACK - The most robust pneumatic nutrunner in its class with 3,100 ft.lbs / 4,100 Nm max. and our most accurate air supply solution**



### Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

### Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
<b>Model</b>	CP6641 + ATC PACK	
<b>Part number</b>	6151800140	
<b>Length</b>	361 mm	14.21"
<b>Height</b>	228 mm	8.97"
<b>Width</b>	100 mm	3.94"
<b>Side to center</b>	40 mm	1.57"
<b>Average air consumption</b>	23 l/s	
<b>Sound pressure</b>	90 db(A)	
<b>Sound Power</b>	101 db(A)	
<b>European Sound standard</b>	ISO 15744	
<b>Sound uncertainty</b>	3 db(A)	
<b>Vibration ISO</b>	ISO 28927-2	
<b>Vibration</b>	<2,5 m/s <sup>2</sup>	
<b>European Directives</b>	2006/42/EC (17/05/2006)	
<b>European Standards</b>	EN ISO 11148-6:2012	
<b>Reaction bar</b>	S-type	

<b>Reversible</b>	Reversible	
<b>Torque preset #</b>	Multi	
<b>Square drive</b>	1"	25 mm
<b>Handle type</b>	Pistol	
<b>Free speed</b>	10 rpm	
<b>Working Torque Range (fwd)</b>	1000 - 4100 Nm	738 - 3100
<b>Working Torque Range (reverse)</b>	1000 - 4100 Nm	738 - 3100
<b>Maximum Torque (fwd)</b>	4100 Nm	3100 ft.lbs
<b>Maximum Torque (reverse)</b>	4100 Nm	3100 ft.lbs
<b>Socket retainer</b>	Hole	
<b>Square drive</b>	25 mm	1"
<b>European Standards</b>	EN ISO 11148-6:2013	
<b>Weight Including Reaction Arm</b>	10.8 kg	23.8 lb
<b>Weight w/o Reaction Arm</b>	8.8 kg	19.4 lb

**CP6641 - The most robust pneumatic nutrunner in its class with 3,100 ft.lbs / 4,100 Nm max.**



### Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

### Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6641	
Part number	6151800110	
Length	361 mm	14.21"
Net weight	8.8 kg	19.4 lb
Height	228 mm	8.97"
Width	100 mm	3.94"
Side to center	40 mm	1.57"
Average air consumption	23 l/s	
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s <sup>2</sup>	
Vibration uncertainty (K)	/ m/s <sup>2</sup>	
European Directives	2006/42/EC (17/05/2006)	

<b>European Standards</b>	EN ISO 11148-6:2012	
<b>Reaction bar</b>	S-type	
<b>Reversible</b>	Reversible	
<b>Torque preset #</b>	Multi	
<b>Square drive</b>	1"	25 mm
<b>Handle type</b>	Pistol	
<b>Free speed</b>	10 rpm	
<b>Working Torque Range (fwd)</b>	1000 - 4100 Nm	738 - 3100
<b>Working Torque Range (reverse)</b>	1000 - 4100 Nm	738 - 3100
<b>Maximum Torque (fwd)</b>	4100 Nm	3100 ft.lbs
<b>Maximum Torque (reverse)</b>	4100 Nm	3100 ft.lbs
<b>Socket retainer</b>	Hole	
<b>Square drive</b>	25 mm	1"
<b>Sound DBA pressure</b>	90 db(A)	
<b>European Standards</b>	EN ISO 11148-6:2013	
<b>Weight Including Reaction Arm</b>	10.8 kg	23.8 lb
<b>Weight w/o Reaction Arm</b>	8.8 kg	19.4 lb