



CP7600C-R - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>
- ▶ Short version with CUPS reaction bar in option

| Technical description | | |
|--------------------------------|---------------------|------------|
| Model | CP7600C-R | |
| Part number | 8941076031 | |
| Length | 345 mm | 13.6" |
| Net weight | 7.4 kg | 16.3 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| European Directives | 2006/42/EC | |
| European Standards | EN ISO 11148-6:2012 | |
| Reaction bar | C reaction bar | |
| Reversible | Reversible | |
| Torque preset # | 1 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | 330 - 660 |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |

CP7600C-R4P - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <2,5 m/s²
- ▶ Short version with CUPS reaction bar in option

| Technical description | | |
|---------------------------------------|---------------------|------------|
| Model | CP7600C-R4P | |
| Part number | 8941076035 | |
| Length | 380 mm | 15" |
| Net weight | 7.7 kg | 17 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| European Directives | 2006/42/EC | |
| European Standards | EN ISO 11148-6:2012 | |
| Reaction bar | C reaction bar | |
| Reversible | Reversible | |
| Torque preset # | 4 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | 330 - 660 |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |

CP7600xB-R4P - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <2,5 m/s²

| Technical description | | |
|---------------------------------------|---------------------|------------|
| Model | CP7600xB-R4P | |
| Part number | 8941076015 | |
| Length | 380 mm | 15" |
| Net weight | 6.9 kg | 15.2 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| European Directives | 2006/42/EC | |
| European Standards | EN ISO 11148-6:2012 | |
| Reaction bar | xB reaction bar | |
| Reversible | Reversible | |
| Torque preset # | 4 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |



CP7600xB-R - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque
- ▶ Accurate torque
- ▶ Operator's comfort for more productivity
- ▶ Fast rundown

Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>

| Technical description | | |
|--------------------------------|---------------------|------------|
| Model | CP7600xB-R | |
| Part number | 8941076011 | |
| Length | 345 mm | 13.6" |
| Net weight | 6.6 kg | 14.6 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| European Directives | 2006/42/EC | |
| European Standards | EN ISO 11148-6:2012 | |
| Reaction bar | xB reaction bar | |
| Reversible | Reversible | |
| Torque preset # | 1 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | 330 - 660 |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |



CP7600xB - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque
- ▶ Accurate torque
- ▶ Increased operator comfort for greater productivity
- ▶ Fast rundown

Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>



| Technical description | | |
|--------------------------------|---------------------|------------|
| Model | CP7600xB | |
| Part number | 8941076010 | |
| Length | 328 mm | 12.9" |
| Net weight | 6 kg | 13.2 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| European Directives | 2006/42/EC | |
| European Standards | EN ISO 11148-6:2012 | |
| Reaction bar | xB reaction bar | |
| Reversible | Non reversible | |
| Torque preset # | 1 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | 330 - 660 |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |

CP7600xC-R4P - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque
- ▶ Accurate torque
- ▶ Operator's comfort for more productivity
- ▶ Fast rundown

Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <2,5 m/s²
- ▶ Extended version with included spring load cup reaction bar



| Technical description | | |
|---------------------------------------|-----------------|------------|
| Model | CP7600xC-R4P | |
| Part number | 8941076025 | |
| Length | 495 mm | 19.5" |
| Net weight | 9.1 kg | 20.1 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| Reaction bar | xC reaction bar | |
| Reversible | Reversible | |
| Torque preset # | 4 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | 330 - 660 |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |

CP7600xC-R - Our most ergonomic & efficient solution for trucks and buses wheel maintenance

Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>
- ▶ Extended version with included spring load cup reaction bar



| Technical description | | |
|---------------------------------------|-----------------|------------|
| Model | CP7600xC-R | |
| Part number | 8941076021 | |
| Length | 460 mm | 18.1" |
| Net weight | 8.8 kg | 19.4 lb |
| Free speed air consumption | 19 l/s | 40 cfm |
| Sound pressure | 79 db(A) | |
| Sound Power | 90 db(A) | |
| Vibration ISO | ISO-28927-2 | |
| Reaction bar | xC reaction bar | |
| Reversible | Reversible | |
| Torque preset # | 1 | |
| Square drive | 1" | |
| Handle type | Pistol | |
| Free speed | 100 rpm | |
| Working Torque Range (fwd) | 450 - 900 Nm | 330 - 660 |
| Working Torque Range (reverse) | 450 - 900 Nm | 330 - 660 |
| Maximum Torque (fwd) | 900 Nm | 660 ft.lbs |
| Maximum Torque (reverse) | 900 Nm | 660 ft.lbs |
| Socket retainer | Hole | |