



960-220AUS & 960-220AUSL POWERIG®

Huck® Hydraulic Power Source

Howmet Fastening Systems introduce two new models to the Huck hydraulic Powerigs® range. The 960-220AUS & 960-220AUSL units are portable, electrically operated and designed to operate all Huck hydraulic equipment.

Features:

- ✓ Brushless, maintenance-free sealed motor for lower operating costs
- ✓ 25% faster installation for increased productivity
- ✓ Lower operating temperatures due to the compact, fan-cooled heat exchanger
- ✓ Quick, simple, and precise pressure adjustments with the built-in pressure gauge
- ✓ New roll cage with carry handles for a safe and easy two-person lift
- ✓ Quieter operation



The 960-220AUSL includes a selector switch which offers an automated installation cycle for Bobtail® fasteners, simplifying Bobtail installation for the operator.

Both these units can be manufactured for use with either single or three-phase electrical supply.

Specifications:

Width: 450mm (17.75 inches)
Length: 450mm (17.75 inches)
Height: 470mm (18.50 inches)
Weight: 30 kgs (66 lbs)
Electrical System: 230 volts, 50/60 Hertz, Single Phase, AC
Control System: Solenoid Operated Directional Valve
Motor: 1400 RPM, 1.5 HP
Pump: 3 Stage. Piston type (Output pressure adjustable to 700 BAR or 10,000 psi)
Reservoir Capacity: 10 Litres (2.6 gallons)
Min. Operating Temp: (ambient) 0°F (18°C)
Max Hydraulic Fluid Temp: 65°C (150°F)



Ph 1300 363 049 | hfsmel.sales@howmet.com